



23-600: Stainless Steel Expansion Tank Gauges



Overview

Holds all 316 stainless steel-compatible liquids. In lower arm: shut-off valve and stainless steel drain valve.

Features

- Two stainless steel guard rods
- High pressure glass standard
- CRN Registered
- 250 psig at 406°F: maximum working pressure (NOTE: Service ratings are subject to pressure / temperature ratings of gauge glass and glass gaskets. Regular gauge glass is used in the standard water gauges unless otherwise noted as red line or high pressure.)

Dimensions

| Part No. | Size | WT/100 lbs./kg | GLASS O D & LENGTH | Wheel Type |
|-----------|-----------|--------------------|------------------------|------------|
| 23-651-00 | 1/2 15 | 225.000 102.058 | 5/8" x 12" 16 x 300 | Aluminum |
| 23-654-00 | 3/4 20 | 225.000 102.058 | 5/8" x 12" 16 x 300 | Aluminum |

Options

| Suffix Number | Specification |
|---------------|--|
| -00 | Standard Gauge w/ Standard Glass & Rod |
| -01 | Top only |
| -02 | Bottom only |
| -03 | Standard Gauge Less Glass and Rod |
| -10 | For Special Gauges and Gauges With Non-Standard Glass and Rod Lengths |
| NOTE | Service ratings are subject to pressure / temperature ratings of gauge glass. Regular gauge glass is used in the standard water gauges unless otherwise noted as red line or high pressure |